



WitchDoctor's Billet Specialties LLC

Billet Grips

[www.buywitchdoctors.com](http://www.buywitchdoctors.com)



**Attention:**

This is an install at your own risk item. If you are not capable of installing it successfully then we suggest you take this item to a professional shop. **TOOLS NEEDED:** 3/32 allen wrench, Phillips screwdriver, channel locks or vise grips, solvent to remove glue on handlebars.

1. Remove stock grips. Left side can be removed by cutting or using channel locks or vise grips and twisting the grip off. Yes the grip will be ruined. Remove any glue residue with the solvent.
2. For the throttle side, its easier to loosen the handlebar risers so that the bars can be moved back to create some slack in the cables.
3. Use a Phillips screwdriver to remove the screws from the switch housing. Once separated, remove the throttle cables from the stock grips.
4. Before installing the new throttle/grip you should spray some silicone on the handlebar area that the grip will twist on. Its also a good time to lube the throttle cable.
5. Feed the throttle cable into the guides in the new throttle/grip.
6. Re-install the switch housing. Be careful not to pinch the electrical lead. Tighten the screws. Check the throttle for binding or sticking BEFORE you start the bike.
7. Install the left side grip using the set screws to hold the grip to the bar. You may want to add some medium strength thread lock to these screws but its not necessary.
8. Adjust and tighten handlebar risers.