

## INSTALLATION INSTRUCTIONS

### CALIPER COVER FOR VICTORY, GLOSS BLACK

7447

#### THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

**WARNING** THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

**CAUTION** THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

**NOTICE** THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

#### ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- |   |                           |   |   |
|---|---------------------------|---|---|
| 1 | Left Brake Caliper Cover  | 1 | Hardware Kit, containing:                   |
| 1 | Right Brake Caliper Cover | 4 | M5 x 0.8 x 8mm Black Button Head Cap Screws |
| 1 | Left Bracket              | 2 | Caliper Pins                                |
| 1 | Right Bracket             | 2 | M4 x 0.7 x 10mm Button Socket Cap Screws    |
| 2 | Alcohol Pads              |   |   |



#### YOU WILL ALSO NEED:

Clean Rag and Warm Soapy Water, Metric Hex Set, Metric Socket Set, Blue Loctite

**NOTICE** THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

**STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.

**STEP 2** Refer to PIC 2 and 3. Remove existing caliper pin and retaining bracket. Set the bracket aside, it will be reused.



## INSTALLATION INSTRUCTIONS

### CALIPER COVER FOR VICTORY, GLOSS BLACK

7447

-CONTINUED-

- STEP 3** Locate provided Caliper Pin. Remove the rubber o-ring from the end of it.
- STEP 4** Align the bracket, that was removed in Step 2, and insert the provided Caliper Pin. Place the rubber o-ring back on the end of the caliper pin. Fully tighten Caliper Pin.

**TORQUE VALUE OF CALIPER PIN:**  
120 IN-LBS (13.6 NM)

#### NOTICE

ENSURE PROPER ADHESION OF THIS PRODUCT. REMOVE ALL GREASE, OIL, BUGS, DIRT, AND OTHER DEBRIS (INCLUDING WAX AND POLISH) FROM THE INSTALLATION AREA. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST OR DAMAGED DUE TO IMPROPER INSTALLATION.


DO NOT ATTEMPT THIS INSTALLATION IN TEMPERATURES BELOW 50°F (10°C). PROPER ADHESIVE BONDING ONLY OCCURS ABOVE 50°F (10°C).

- STEP 5** Refer to PIC 6. Using warm soapy water and a clean rag, remove all dirt and debris from the installation area; allow the area to dry completely.
- Wipe the installation area with the included alcohol pads to remove any wax or polish; allow the area to dry completely.
- STEP 6** Refer to PIC 7. Locate the Left Bracket. The end with the notch located near the mounting hole is the top end of the bracket.
- STEP 7** Test fit the Left Bracket over the left (clutch) side caliper; remove the bracket.
- STEP 8** Use your fingernail to rub the adhesive backing on the back of the bracket; this will activate the adhesive. Remove and discard the backing.
- STEP 9** Refer to PIC 8. Align the Left Bracket over the left caliper; press into place for one minute; full bonding will occur after 24 hours.

*Note: If the bike is going to be operated before full bonding occurs, secure the Right Bracket to the bike with a good quality masking or painter's tape.*

- STEP 10** Locate provided one (1) M4 x 0.7 x 10mm Button Socket Cap Screw. Apply a small amount of Blue Loctite to the screw.
- STEP 11** Refer to PIC 8. Secure the bracket to the caliper by inserting the screw through the mounting hole that is aligned with the Caliper Pin. Fully fasten hardware.
- STEP 12** Locate provided Left Brake Caliper Cover and two (2) M5 x 0.8 x 8mm Black Button Head Cap Screws. Apply a small amount of Blue Loctite to the screws.
- STEP 13** Refer to PIC 9. Align the caliper cover over the installed caliper bracket. Fasten the cover to the bracket using the M5 screws.
- STEP 14** Repeat steps 2 through 12 on the opposite side.

PIC 4



PIC 5

O-RING

PIC 6




PIC 7

NOTCH



PIC 8



M4 BSCS

PIC 9



M5 BHCS

**KURYAKYN.COM**

866 277 9598 | INFO@KURYAKYN.COM  
454 COUNTY ROAD VV SOMERSET, WI 54025



## INSTALLATION INSTRUCTIONS

### CALIPER COVER FOR VICTORY, GLOSS BLACK

7447

-CONTINUED-

#### NOTICE

IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.



#### LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials & workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

1. Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
2. The product must be properly installed, maintained & operated under normal conditions.
3. Kuryakyn shall not be liable for any consequential & incidental damages, including labor & paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn & a customer.
4. Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
5. Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'s contained in components of Kuryakyn products will be warranted for defects in materials & workmanship for 3 years from the date of purchase whereas all other components shall be warranted for one (1) year.
6. All warranty claims must be directed to the place of purchase. Merchandise sold through internet auction sites or any other unauthorized reseller shall not carry a Kuryakyn warranty. If unsure, please contact the place of purchase to verify they are an authorized Kuryakyn reseller.

#### RETURN POLICY

Merchandise determined to be defective may be returned up to one year from the date of purchase. Returns must be processed through original seller. Returned merchandise for any other reason other than warranty claims must be in like new condition & subject to a 20% restocking fee. All returns are subject to inspection for determination of full or partial credit. Any returned part that shows evidence of being used or installed contrary to manufacturer's instructions, &/or subjected to improper handling, packaging or return shipping by the customer, will not be eligible for exchange, refund or warranty consideration. All returned electrical items will be inspected & tested. If electrical item is deemed functional, no credit will be issued & item will be returned. All sales are final on discontinued or closeout merchandise.

©2015 KURYAKYN HOLDINGS, LLC ALL RIGHTS RESERVED

KURYAKYN, KURYAKYN K logo and the marks appearing on this instruction sheet are registered and common law trademarks of Kuryakyn Holdings except noted third-party trademarks. A full listing of trademarks and trademark registrations owned by Kuryakyn Holdings can be found at [www.kuryakyn.com/legal-notice](http://www.kuryakyn.com/legal-notice).

Emissions Notice: The California Air Resources Board (CARB) does not permit the use of aftermarket emission-related parts (s) that alter the performance of OEM emission-related devices unless CARB has issued an Executive Order, other than on racing vehicles on closed courses. Check your local laws and manufacturer's information.

Listed Manufacturers and product model names are for reference only. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. All specifications are subject to change without notice.

For additional information on third-party product and company names, please consult our Web page at [www.kuryakyn.com/legal-notice](http://www.kuryakyn.com/legal-notice)